




## Features

- RJ-11 contacts are plated with 50 microns of hard gold
- Two circuit board slots for mounting MTUs, RIDs or half-ringer electronic devices
- Tamper resistant stainless steel security (KS) screw in Telco cover
- Secure, user friendly terminations for IW and line cord wiring
- Numerous knockout ports for easy assembly to utility boxes
- Accommodates Bourns and other manufacturer's station protectors
-  Listed per UL 497 (File: E53117)

## 708X Series – Network Interface Device

Bourns 708X Series NID is designed to be used as a two-line unit to eliminate the necessity of upgrading kits. The installer simply needs to add the Station Protector and connect the internal wiring when activating the second line. This model can be installed outside, as a stand-alone unit (Model 7081) or indoors with the outside cover removed (Model 7080). This NID is designed to fit a variety of existing or contractor provided flush mounted utility boxes.

The Model 708X Series two line NID is manufactured of flame retardant, high-impact resistant, ultraviolet-desensitized plastic.

### How to Order

708X - XX - X X

#### Model Number Options

- 0 = No outside cover
- 1 = With outside cover
- 2 = One line only

#### Number of Protectors

- 01 = One Protector
- 02 = Two Protectors

#### Protector Options

- D<sup>1</sup> = 455HS-MSP (2377-45-HS) Voice/Data/DSL (UL,cUL)
- U<sup>3</sup> = 455HS-MSP (2377-45-HS-IDC) Voice/DSL/Data (UL,cUL)
- Z<sup>1</sup> = 455HS-BC\* (2377-45-BC) Balance-Sensitive DSL (UL, cUL)
- W<sup>3</sup> = 455HS-BC\* (2377-45-BC-IDC) Balance-Sensitive DSL (UL, cUL)
- V<sup>3</sup> = 455-MSP-TBU\* (2377-45-HS-TBU) MSP w/TBU® Protector (UL, cUL)
- Q<sup>3</sup> = 455BC-MSP-TBU\* (2377-45-BC-TBU) Balance-Sensitive MSP w/TBU® Protector (UL, cUL)
- E<sup>2</sup> = 155HS-MSP (2378-35-HS) Voice/DSL/Data (UL, cUL)
- Y<sup>2</sup> = 155HS-BC\* (2378-35-BC) Balance-Sensitive DSL (UL, cUL)
- K = 356G (2377-35-G) Balanced GDT, No Back-Up-Gap (UL, cUL)
- R<sup>3</sup> = 356G (2377-35-G-IDC) Balanced GDT, No Back-Up-Gap (UL, cUL)
- B = 125EW (2374-01) Dual Gas Tube (UL, cUL, Telcordia)
- C = 125EW-R (2375-01) Dual Gas Tube (UL, cUL, RUS)
- L = 356M (2377-01) Balanced Gas Tube (UL, cUL, RUS)
- T = Tii355M
- O = No Station Protectors (Not available with DSL configurations)

\*For DSL systems requiring capacitive balance within 1 pF.

Note 1 = Digi.Guard - 356 size, RUS Maximum Duty

Note 2 = Digi.Guard II - 125 size, RUS Heavy Duty

Note 3 = Insulation Displacement Connectors (IDC)

#### Special Options

- O = No options

### Product Dimensions

High	Wide	Deep
$\frac{167.6}{(6.6)}$	$\frac{88.9}{(3.5)}$	$\frac{50.8}{(2.0)}$

DIMENSIONS:  $\frac{\text{MM}}{\text{(INCHES)}}$

# BOURNS®

**Asia-Pacific:** Tel: +886-2 2562-4117 • Fax: +886-2 2562-4116

**Europe:** Tel: +41-41 768 5555 • Fax: +41-41 768 5510

**The Americas:** Tel: +1-951 781-5500 • Fax: +1-951 781-5700

[www.bourns.com](http://www.bourns.com)

REV. H 03/11

Specifications are subject to change without notice.

Customers should verify actual device performance in their specific applications.